



Ultra-low phase-noise microwave with optical frequency combs

**X. Xie¹, D. Nicolodi¹, R. Bouchand¹, M. Giunta², M. Lezius², W. Hänsel²,
R. Holzwarth², A. Joshi³, S. Datta³, P. Tremblin⁴, C. Alexandre⁵ G. Santarelli⁴
and Y. Le Coq¹**

¹LNE-SYRTE, Observatoire de Paris, CNRS, UPMC, France

²Menlo Systems GmbH, Martinsried, Germany

³Discovery Semiconductors, Ewing, NJ, USA.

⁴LP2N, Institut d'Optique Graduate School, CNRS, Univ. de Bordeaux, France.

⁵CNAM, Laboratoire Cedric, France



PHOTONIC μW GENERATION W/ FREQUENCY COMBS


Frequency Combs is frequency divider from optics-to- μW

200THz to 10GHz

$N \sim 20000$



PN reduced by N^2

$20 \log(N) \sim 86\text{dB}$





- ✓ no cryogenic, easy operation, potentially compact
- ✓ very phase low noise low&high Fourier frequencies
- ✓ multiple output microwave frequencies, tunable


REPETITION RATE MULTIPLICATION



- ✓ Suppression of unwanted harmonics
- ✓ Simpler microwave filtering



PHASE NOISE PSD CROSS CORRELATION MEASUREMENTS



Up to 3 cw USL at 1.5 μ m loosely frequency locked
 3 comb-based μ wave generation

We need to develop only one system



PHASE NOISE PSD@12GHz

